

Centurion Interiors
Partition Systems

Demountable Partitions
Glass Partitions
Acoustic Glass Doors
Timber Doors
Bespoke Solutions



Operation and Maintenance Manual

System 2000, 3000, 4000, 9000, 9000FR & XP

Operation and Maintenance Manual

SYSTEM 2000, 3000, 4000, 9000, 9000FR & XP

ALL POLYESTER POWDER COATED & PVC SECTIONS, POLISHED METAL AND LAMINATE FACINGS

- Cleaning:** Abrasive cleaners should not be used.
An occasional wipe using a mild detergent solution, rinse with a clean damp Cloth (avoid over – wetting), and then buff with a clean dry cloth.
Cleaning liquids should be wiped away completely or staining may appear on adjacent surfaces.
- Repair:** Superficial damage – painted items can be re-painted with touch up paint, Other items no treatment possible.
Substantial damage – replace component.

WALL PANEL FACINGS

- Cleaning:** See manufacturers instruction for individual types. Some fabric materials may shrink if liquid cleaners are used.
- Repair:** Superficial damage – painted surfaces should be filled with appropriate filler,sanded smooth and repainted. Vinyl finishes should be filled as above and re-fix or patch vinyl with a PVA based adhesive.
Substantial damage – replace component.

GLASS SURFACES

- Cleaning:** Use proprietary glass cleaner for any glass surface, avoid abrasive materials, and avoid excessive amounts of water. Use a clean, dry, lint-free soft cloth, water and a mild detergent.
Cleaning liquids should be wiped away completely or staining may appear on adjacent surfaces.
- Repair:** Superficial damage – no repair possible.
Substantial damage – replace component.

MOVING PARTS

- Cleaning:** Prior to installing glazing, the inside of the tracks should be brushed or wiped clean.
- Maintenance:** Door Hinges, Inspect, adjust if necessary and lubricate every six months or more frequently in a dry area. Lock mechanisms should be lightly oiled during use as required with excess lubricant wiped away. Door closers, inspect, adjust if necessary to prevent slamming or ensure correct closing and lubricate every six months or more frequently in a dry area. Do not wedge in an open position, as this can damage the seals and cause oil leakage. In fire rated constructions, this practice would contravene the fire regulations.
- Repair:** Damage to hinges, lock mechanisms, ironmongery or door closers will necessitate replacement.

ELECTRICAL

Care should be taken when cleaning with liquids in close proximity to electrical switchgear or outlets to avoid contact. Servicing should only be carried out by a qualified electrician.

HANDLING AND SAFETY DATA

For general handling and safety data refer to the product safety data sheet.

TECHNICAL MANUAL

For all Technical information refer to Technical Manual.

INSTALLATION GUIDE

For method of build refer to the Installation guides.

Contact Us:



Birmingham

NDI, Meridian Way
Core 42 Logistics Park
Watling Street
Tamworth
B78 1TX

T: 01213 522 460
E: birmingham@ndi.co.uk

London

NDI, Unit 18, IO Centre
Kimpton Park Way
Sutton
SM3 9BW

T: 020 8254 2380
E: london@ndi.co.uk

Maidstone

NDI, Loc8,
Unit 12
Maidstone
ME17 1XG

T: 01622 790 622
E: maidstone@ndi.co.uk

Milton Keynes

NDI, Unit 2, Bilton Road
Denby East
Bletchley
MK1 1HW

T: 01908 640 634
E: milton.keynes@ndi.co.uk

Newport

NDI, Unit 4
Tregwilym Road
Rogerstone
Newport
NP10 9DQ

T: 01633 898 340
E: newport@ndi.co.uk

Newton-Le-Willows

NDI, Unit 7
Anglezarke Road
Newton Le Willows
WA12 8DJ

T: 01925 220 827
E: newtonsales@ndi.co.uk

Poole

NDI, Albany House
Elliot Road
Poole
BH11 8JH

T: 01202 576 006
E: poole@ndi.co.uk

ndi.co.uk

Disclaimer

IT IS IMPORTANT THAT YOU READ AND UNDERSTAND THIS STATEMENT BEFORE MAKING USE OF THIS DOCUMENT.

This document is published by Truline Systems. The information contained within this publication is for general information purposes only. The publication has not been prepared to meet the individual requirements of any particular construction project and it is your responsibility to ensure that the construction materials, techniques and processes are suitable for that particular use.

The information contained within this publication is not intended to amount to, nor should it be relied upon as, formal advice or guidance (including from any qualified professional).

The information provided is only to be used and acted on by, or under the supervision of suitably qualified individuals and is correct at the time of going to press. However Truline Systems reserves the right to amend specifications without prior notification in accordance with our policy of continuous development.

The information in this publication is not to be used as a substitute for obtaining suitable independent, professional, qualified and/or specialist advice. If you are not a suitably qualified professional, you must obtain your own independent, specialist advice from a relevant qualified professional for any construction project.

Truline Systems shall not be liable for any loss of profit, revenue, business, contract, opportunity, goodwill, reputation, or any indirect, special or consequential loss arising out of, or in connection with, this publication.

If you have any queries, please contact technical@trulinesystems.co.uk